

2022

An Investigation into whether psychopathic traits negatively contribute to moral judgements

Esser, M.

Esser, M. (2022) 'An Investigation into whether psychopathic traits negatively contribute to moral judgements', *The Plymouth Student Scientist*, 15(2), pp. 547-562.

<http://hdl.handle.net/10026.1/20106>

University of Plymouth

All content in PEARL is protected by copyright law. Author manuscripts are made available in accordance with publisher policies. Please cite only the published version using the details provided on the item record or document. In the absence of an open licence (e.g. Creative Commons), permissions for further reuse of content should be sought from the publisher or author.

Appendices

Appendix A. URL link to data set

This item was original stored on a MS OneDrive (link has been removed).

Appendix B. R Studio Analysis Script

```
# Generic Qualtrics Data Import library(tidyverse) library(lubridate)
library(psych)

# change the string to the name of your data file
datafile <- 'Psychopathy and Morality_February 3, 2022_03.42.csv'

# first row of the file has variable names, second has item text, and third has junk. Data starts
on row 4

# so first read the first row into a vector containing the variable names col_names <-
names(read_csv(datafile, n_max = 0))

# then read the item text from second row
items<- names(read_csv(datafile,skip=1, n_max=0))

# and name these with the variable names names(items)<-col_names

colclasses<-c("POSIXct", "POSIXct", "chr", "chr", "num", "num", "logi", "POSIXct", "chr",
rep("logi",4), "num", "num", rep("chr",4), "Date", rep("chr", 89))

# and then read in everything else skipping rows 1 to 3 survey<-read_csv(datafile, col_names
= col_names, skip = 3,

col_types = cols (.default = "c"))

#changing DOB to age
survey$DOB <-dmy(survey$DOB)
survey$StartDate <-as.Date(ymd_hms(survey$StartDate)) survey$age <-
as.numeric((survey$StartDate - survey$DOB)/365)

#remove pilot data
survey<-survey %>% filter(StartDate> dmy("01/01/2022"))

mean(survey.recode$age) #Mapping variables

mapping.list1 <- c("False" = 0, "Somewhat false" = 1, "Somewhat true" = 2, "True" = 3)
mapping.list2 <- c("Not at all relevant" = 0, "Not very relevant" = 1, "Slightly relevant" = 2,
"Somewhat relevant" = 3, "Very relevant" = 4, "Extremely relevant" = 5)
mapping.list3 <- c("Strongly disagree" = 0, "Moderately disagree" = 1, "Slightly disagree" =
2, "Slightly agree" = 3, "Moderately agree" = 4, "Strongly agree" = 5)
```

```
mapping.list1r <- c("False" = 3, "Somewhat false" = 2, "Somewhat true" = 1, "True" = 0)
mapping.list2r <- c("Not at all relevant" = 5, "Not very relevant" = 4, "Slightly relevant" = 3,
"Somewhat relevant" = 2, "Very relevant" = 1, "Extremely relevant" = 0)
mapping.list3r <- c("Strongly disagree" = 5, "Moderately disagree" = 4, "Slightly disagree" =
3, "Slightly agree" = 2, "Moderately agree" = 1, "Strongly agree" = 0)
```

```
#Recoding Variables survey.recode <- survey %>%
```

```
mutate(
```

```
TriPM1_1 = recode(TriPM1_1, !!!mapping.list1), TriPM1_2 = recode(TriPM1_2,
!!!mapping.list1r), TriPM1_3 = recode(TriPM1_3, !!!mapping.list1), TriPM1_4 =
recode(TriPM1_4, !!!mapping.list1r), TriPM1_5 = recode(TriPM1_5, !!!mapping.list1),
TriPM1_6 = recode(TriPM1_6, !!!mapping.list1), TriPM1_7 = recode(TriPM1_7,
!!!mapping.list1), TriPM1_8 = recode(TriPM1_8, !!!mapping.list1), TriPM2_1 =
recode(TriPM2_1, !!!mapping.list1), TriPM2_2 = recode(TriPM2_2, !!!mapping.list1r),
TriPM2_3 = recode(TriPM2_3, !!!mapping.list1r), TriPM2_4 = recode(TriPM2_4,
!!!mapping.list1), TriPM2_5 = recode(TriPM2_5, !!!mapping.list1), TriPM2_6 =
recode(TriPM2_6, !!!mapping.list1), TriPM2_7 = recode(TriPM2_7, !!!mapping.list1),
TriPM2_8 = recode(TriPM2_8, !!!mapping.list1r), TriPM3_1 = recode(TriPM3_1,
!!!mapping.list1), TriPM3_2 = recode(TriPM3_2, !!!mapping.list1), TriPM3_3 =
recode(TriPM3_3, !!!mapping.list1), TriPM3_4 = recode(TriPM3_4, !!!mapping.list1),
TriPM3_5 = recode(TriPM3_5, !!!mapping.list1r), TriPM3_6 = recode(TriPM3_6,
!!!mapping.list1), TriPM3_7 = recode(TriPM3_7, !!!mapping.list1), TriPM3_8 =
recode(TriPM3_8, !!!mapping.list1), TriPM4_1 = recode(TriPM4_1, !!!mapping.list1r),
TriPM4_2 = recode(TriPM4_2, !!!mapping.list1), TriPM4_3 = recode(TriPM4_3,
!!!mapping.list1), TriPM4_4 = recode(TriPM4_4, !!!mapping.list1), TriPM4_5 =
recode(TriPM4_5, !!!mapping.list1), TriPM4_6 = recode(TriPM4_6, !!!mapping.list1r),
TriPM4_7 = recode(TriPM4_7, !!!mapping.list1), TriPM4_8 = recode(TriPM4_8,
!!!mapping.list1), TriPM5_1 = recode(TriPM5_1, !!!mapping.list1r), TriPM5_2 =
recode(TriPM5_2, !!!mapping.list1), TriPM5_3 = recode(TriPM5_3, !!!mapping.list1r),
```

```
TriPM5_4 = recode(TriPM5_4, !!!mapping.list1), TriPM5_5 = recode(TriPM5_5,
!!!mapping.list1), TriPM5_6 = recode(TriPM5_6, !!!mapping.list1), TriPM5_7 =
recode(TriPM5_7, !!!mapping.list1r), TriPM5_8 = recode(TriPM5_8, !!!mapping.list1),
TriPM6_1 = recode(TriPM6_1, !!!mapping.list1r), TriPM6_2 = recode(TriPM6_2,
!!!mapping.list1), TriPM6_3 = recode(TriPM6_3, !!!mapping.list1), TriPM6_4 =
recode(TriPM6_4, !!!mapping.list1r), TriPM6_5 = recode(TriPM6_5, !!!mapping.list1),
TriPM6_6 = recode(TriPM6_6, !!!mapping.list1), TriPM6_7 = recode(TriPM6_7,
!!!mapping.list1r), TriPM6_8 = recode(TriPM6_8, !!!mapping.list1), TriPM7_1 =
recode(TriPM7_1, !!!mapping.list1), TriPM7_2 = recode(TriPM7_2, !!!mapping.list1r),
TriPM7_3 = recode(TriPM7_3, !!!mapping.list1), TriPM7_4 = recode(TriPM7_4,
!!!mapping.list1r), TriPM7_5 = recode(TriPM7_5, !!!mapping.list1), TriPM7_6 =
recode(TriPM7_6, !!!mapping.list1), TriPM7_7 = recode(TriPM7_7, !!!mapping.list1),
TriPM7_8 = recode(TriPM7_8, !!!mapping.list1r), MFQ1_1 = recode(MFQ1_1,
!!!mapping.list2), MFQ1_2 = recode(MFQ1_2, !!!mapping.list2), MFQ1_3 =
recode(MFQ1_3, !!!mapping.list2), MFQ1_4 = recode(MFQ1_4, !!!mapping.list2), MFQ1_5
= recode(MFQ1_5, !!!mapping.list2), MFQ1_6 = recode(MFQ1_6, !!!mapping.list2),
MFQ1_7 = recode(MFQ1_7, !!!mapping.list2), MFQ1_8 = recode(MFQ1_8,
!!!mapping.list2), MFQ2_1 = recode(MFQ2_1, !!!mapping.list2), MFQ2_2 =
recode(MFQ2_2, !!!mapping.list2), MFQ2_3 = recode(MFQ2_3, !!!mapping.list2), MFQ2_4
```

```
= recode(MFQ2_4, !!!mapping.list2), MFQ2_5 = recode(MFQ2_5, !!!mapping.list2),  
MFQ2_6 = recode(MFQ2_6, !!!mapping.list2), MFQ2_7 = recode(MFQ2_7,  
!!!mapping.list2), MFQ2_8 = recode(MFQ2_8, !!!mapping.list2), MFQ3_1 =  
recode(MFQ3_1, !!!mapping.list3), MFQ3_2 = recode(MFQ3_2, !!!mapping.list3), MFQ3_3  
= recode(MFQ3_3, !!!mapping.list3), MFQ3_4 = recode(MFQ3_4, !!!mapping.list3),  
MFQ3_5 = recode(MFQ3_5, !!!mapping.list3), MFQ3_6 = recode(MFQ3_6,  
!!!mapping.list3), MFQ3_7 = recode(MFQ3_7, !!!mapping.list3), MFQ3_8 =  
recode(MFQ3_8, !!!mapping.list3), MFQ4_1 = recode(MFQ4_1, !!!mapping.list3), MFQ4_2  
= recode(MFQ4_2, !!!mapping.list3), MFQ4_3 = recode(MFQ4_3, !!!mapping.list3),  
MFQ4_4 = recode(MFQ4_4, !!!mapping.list3), MFQ4_5 = recode(MFQ4_5,  
!!!mapping.list3),
```

```
MFQ4_6 = recode(MFQ4_6, !!!mapping.list3), MFQ4_7 = recode(MFQ4_7,  
!!!mapping.list3), MFQ4_8 = recode(MFQ4_8, !!!mapping.list3))
```

```
#Selecting columns TriPM Boldness TriPM.boldness <- survey.recode %>%
```

```
select (id, TriPM1_1, TriPM1_4, TriPM1_7, TriPM2_2, TriPM2_5, TriPM2_8,  
TriPM3_3, TriPM3_6, TriPM4_1, TriPM4_4, TriPM4_8,
```

```
TriPM5_3, TriPM5_6, TriPM6_1, TriPM6_4, TriPM6_7, TriPM7_2, TriPM7_5, TriPM7_8)  
%>%
```

```
pivot_longer(TriPM1_1:TriPM7_8) %>% group_by(id) %>%  
summarise(boldness=mean(value, na.rm=T))
```

```
#Selecting columns TriPM Meanness TriPM.meanness <- survey.recode %>%
```

```
select (id, TriPM1_2, TriPM1_6, TriPM1_8, TriPM2_3, TriPM2_6, TriPM3_1, TriPM3_4,  
TriPM3_7, TriPM4_2, TriPM4_5, TriPM5_1,
```

```
TriPM5_4, TriPM5_7, TriPM5_8, TriPM6_2, TriPM6_5, TriPM6_8, TriPM7_4, TriPM7_6)  
%>%
```

```
pivot_longer(TriPM1_2:TriPM7_6) %>% group_by(id) %>%  
summarise(meanness=mean(value, na.rm=T))
```

```
#Selecting columns TriPM Disinhibition TriPM.disinhibition <- survey.recode %>%
```

```
select (id, TriPM1_3, TriPM1_5, TriPM2_1, TriPM2_4, TriPM2_7, TriPM3_2, TriPM3_5,  
TriPM3_8, TriPM4_3, TriPM4_6, TriPM4_7,
```

```
TriPM5_2, TriPM5_5, TriPM6_3, TriPM6_6, TriPM7_1, TriPM7_3, TriPM7_7) %>%  
pivot_longer(TriPM1_3:TriPM7_7) %>%  
group_by(id) %>%  
summarise(disinhibition=mean(value))
```

```
# Joining all TriPM columns together
```

```
TriPM <- left_join(TriPM.boldness, TriPM.meanness) TriPM <- left_join(TriPM,  
TriPM.disinhibition)
```

```
#Selecting columns MFQ Harm MFQ.harm <- survey.recode %>%

select (id, MFQ1_1, MFQ1_7, MFQ2_4, MFQ3_1, MFQ3_7, MFQ4_4) %>%
pivot_longer(MFQ1_1:MFQ4_4) %>%

group_by(id) %>% summarise(harm=mean(value))

#Selecting columns MFQ Fairness MFQ.fairness <- survey.recode %>%

select (id, MFQ1_2, MFQ1_8, MFQ2_5, MFQ3_2, MFQ3_8, MFQ4_5) %>%
pivot_longer(MFQ1_2:MFQ4_5) %>%

group_by(id) %>% summarise(fairness=mean(value))

#Selecting columns MFQ Ingroup MFQ.ingroup <- survey.recode %>%

select (id, MFQ1_3, MFQ2_1, MFQ2_6, MFQ3_3, MFQ4_1, MFQ4_6) %>%
pivot_longer(MFQ1_3:MFQ4_6) %>%

group_by(id) %>% summarise(ingroup=mean(value))

#Selecting columns MFQ Authority MFQ.authority <- survey.recode %>%

select (id, MFQ1_4, MFQ2_2, MFQ2_7, MFQ3_4, MFQ4_2, MFQ4_7) %>%
pivot_longer(MFQ1_4:MFQ4_7) %>%

group_by(id) %>% summarise(authority=mean(value))

#Selecting columns MFQ Purity MFQ.purity <- survey.recode %>%

select (id, MFQ1_5, MFQ2_3, MFQ2_8, MFQ3_5, MFQ4_3, MFQ4_8) %>%
pivot_longer(MFQ1_5:MFQ4_8) %>%

group_by(id) %>% summarise(purity=mean(value))

# Joining all MFQ columns together
MFQ1 <- left_join(MFQ.harm, MFQ.fairness, by="id")

MFQ2 <- left_join(MFQ1, MFQ.ingroup, by="id") MFQ3 <- left_join(MFQ2,
MFQ.authority, by="id") MFQ <- left_join(MFQ3, MFQ.purity, by="id")

TriPM <- TriPM %>% filter(!id==23490) %>% filter(!id==23316) MFQ <- MFQ %>%
filter(!id==23490) %>% filter(!id==23316) TriPMMFQ <- left_join(TriPM, MFQ, by="id")
#correlation matrix

pairs.panels(TriPM %>% select(-id),lm=TRUE,stars=T)

pairs.panels(MFQ %>% select(-id),lm=TRUE,stars=T) corr.test(MFQ$harm,MFQ$fairness)
```

```
corr.test(MFQ$authority,MFQ$purity) pairs.panels(TriPMMFQ %>% select(-id),lm=TRUE,stars=T)
```

```
TriPM.total<-TriPM %>% pivot_longer(boldness:disinhibition) %>% group_by(id) %>% summarise(TriPM=sum(value))
```

```
MFQ.total<-MFQ %>% pivot_longer(harm:purity) %>% group_by(id) %>% summarise(MFQ=sum(value))
```

```
Totals <- left_join(MFQ.total, TriPM.total, by="id") corr.test(Totals$MFQ, Totals$TriPM) pairs.panels(Totals %>% select(-id),lm=TRUE,stars=T)
```

```
mean(Totals$TriPM) median(Totals$TriPM) SD(Totals$TriPM)
```

```
median(TriPM$boldness) mean(TriPM$boldness) SD(TriPM$boldness)
```

```
median(TriPM$meanness) mean(TriPM$meanness) SD(TriPM$meanness)
```

```
median(TriPM$disinhibition) mean(TriPM$disinhibition) SD(TriPM$disinhibition)
```

```
mean(Totals$MFQ) median(Totals$MFQ) SD(Totals$MFQ)
```

```
median(MFQ$harm) mean(MFQ$harm) SD(MFQ$harm)
```

```
median(MFQ$fairness) mean(MFQ$fairness) SD(MFQ$fairness)
```

```
median(MFQ$ingroup) mean(MFQ$ingroup) SD(MFQ$ingroup)
```

```
median(MFQ$authority) mean(MFQ$authority) SD(MFQ$authority)
```

```
median(MFQ$purity) mean(MFQ$purity) SD(MFQ$purity)
```